

## AT-MCU-16P

### MEDIA CONVERTER RACK



#### PRODUCT OVERVIEW

**AT-MCU-16P** series is cost-effective media converter rack (2U) widely used in the equipment room. Different types of standalone type media converter developed by our company can be inserted into this rack, which total slots up to 14. It is furnished with two power supplies: main power supply and spare one, and supports its automatic switch-over.

#### FEATURES

- High quality 19" chassis-Mountable Chassis installation.
- Supports up to 14 hot-swappable media converters.
- Each power supply with one fan which brings the air-flow for system cooling.
- Two power slots at rear panel for redundant power support with options of AC or DC supplies.
- Bay power isolation, ensure each bay is electrically isolated from each other.
- Support multiple converters with 10/100/1000Mbps, copper, fiber, single/multi-mode, ST/SC/SFP connectors.
- Reduce the effort of converter maintenance and management, diagnose the status at one time.
- Cost-effective, easy install.
- Conforms to FCC, CE, and RoHS

#### APPLICATION

- Network Communication
- FTTH / FTTB / FTTx
- ISP Backhaul Networking

#### TECHNICAL SPECIFICATIONS

Parameter	Specifications
Number of slots	14
Structure	2U rack
Power input	AC Voltage: AC 100~265V; frequency: 50/60 Hz DC Voltage: DC 40~70V
Power output	DC5V 12A

Anda Telecom Pvt. Ltd.

Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone : +91 120 4109590, +91 98716 50366

E-mail : [Info@andatelecom.com](mailto:Info@andatelecom.com) URL : [www.andatelecom.com](http://www.andatelecom.com)

Ripple	≤20mv
Power configuration	Single power supply or Dual power supply
LED indication	POWER (power supply)
Max power consumption	60W for Single power supply; 120W for Dual power supply
Operating temperature	-20~65° C
Operating humidity	5%~90%
Maintaining temperature	-40~70° C
Maintaining humidity	5% ~ 90% non-condensing
Dimensions of rack	427mm* 230mm* 90mm

## ORDER INFORMATION

Model	Description
AT-MCU-16P	19' 2U 14 Slot Chassis with double AC220V Power Supply
AT-MCU-16P	19' 2U 14 Slot Chassis with double DC48V Power Supply
AT-MCU-16P	19' 2U 14 Slot Chassis with AC220V and DC48V Power Supply

## ORDERING INFORMATION: -

<b>Anda Telecom Pvt. Ltd.</b> <b>Registered Office: PLOT NO 38, BLOCK E, -, Sector 6, Noida,</b> <b>Gautambuddha Nagar, Uttar Pradesh, 201301</b> <b>India.</b>	  	<a href="https://andatelecom.com/">https://andatelecom.com/</a> <b>+91 120 4109590 + 91 98716 50366</b> <a href="mailto:info@andatelecomindia.com">info@andatelecomindia.com</a>
--	---	--